

STRONGHOLD 60

HIGH PRESSURE COUPLINGS



The Stronghold 60 range of couplings and plugs is manufactured to the TEMA-style quick release coupling standard used across leading high-pressure cleaning systems. Featuring a straight-through fluid path to minimise turbulence and maintain optimum flow rates, the unique design helps reduce dirt ingress and grease loss, extending coupling service life.

Product	Code
Stronghold 60 Coupling, Stainless Steel, 3/8" Female	1620
Stronghold 60 Coupling, Plated Brass, 3/8" Female	0615
Stronghold 60 Plug, Stainless Steel, 3/8" Female	1621
Stronghold 60 Plug, Mild Steel, 3/8" Female	0616

KEY FEATURES & BENEFITS

- Industry-standard TEMA-style quick release coupling system
- Straight-through flow path maximises fluid flow efficiency
- Unique design helps reduce dirt ingress and grease loss
- Available in plated brass, mild steel and stainless steel versions
- High-grade stainless steel options available for demanding environments
- 10-ball bearing design provides secure connection and extended service life
- Easy operation and maintenance

TECHNICAL DETAILS

Maximum System Pressure	350 Bar
Maximum System Temperature	90°C
Rated Burst Pressure	1200 Bar
Rated Temperature Range	-30°C to 100°C
Flow Path	3/8"
Material Options	316 Stainless Steel, Mild Steel, Passivated Brass
Connection Size	3/8" Female

IMPORTANT NOTE

Pressure and temperature ratings apply to the coupling only and not to the complete hose, lance, gun or assembled system. Overall system ratings depend on the installation and clamping method used.