

TECHNIFOGGER 40L

COMPACT PORTABLE FOGGING MACHINE

TECHNIFOGGER



Extreme strength & durability



High chemical resistance



Safe & Portable non-pressurised tanks

The Technifogger is designed as a highly portable fogger with a non-pressurized tank. By connecting compressed air, the prediluted disinfectant and air are combined, and released into the atmosphere as a fog.

Disinfectant is applied thoroughly and evenly, reaching areas often missed by traditional methods.

The adjustment valve alters the dryness/wetness of the fog.

The Technifogger does not have a pump or moving parts, simply using air pressure to both lift the fluid and inject the air to create the fog.

KEY FEATURES & BENEFITS

- Non-pressurised tank design for safe operation
- Compact and manoeuvrable for use in hard-to-reach areas
- Portable lightweight design with integrated carry handles
- Available in blue, red or white to support colour-coding systems
- Adjustable fog quality to suit different applications
- No pump or moving parts for simplified operation and maintenance

TECHNICAL DETAILS

Weight	12 kg (10 m version, empty)
Compressed Air Requirement	4 - 6 bar
Tank Capacity	40 L
Material	Stainless Steel / PE
Air Consumption	250 - 300 L/min
Fog Output (Liquid)	Approx. 1 L/min
Particle Size	<1 - 100 micron
Room Size Coverage	Up to 1,600 m ³ (5 m ceiling height)

Product	Blue	Red	White
Technifogger 40L	9294	9295	9296

NOTES:

The above figures are based on a full tank of liquid and will take approximately 40-50 minutes to achieve, depending on air supply and liquid viscosity.