

ULTRAWASH 2 WIRE WASHDOWN HOSE



KEY FEATURES & BENEFITS

- Lightweight design for easier handling
- Flexible construction for improved manoeuvrability
- High-pressure performance up to 400 bar (5600 PSI)
- Suitable for demanding food industry environments
- Available in blue and red colour options

TECHNICAL DETAILS

Pressure Rating	400 bar (5600 PSI)
Temperature Rating	-40°C to +121°C
Weight	0.5 kg/m
Outside Diameter	18.8 mm
Minimum Bend Radius	127 mm

The Ultrawash 2 Wire Washdown Hose is designed for demanding food industry washdown applications. Featuring a smooth nitrile cover and twin-wire construction, it delivers excellent durability and long service life while resisting chemical and grease damage.

The non-marking cover helps protect floors and surfaces, making it ideal for hygiene-critical environments.

Product	Blue	Red
10m 3/8" 2W Ultrawash Hose	0414	0908
15m 3/8" 2W Ultrawash Hose	0415	0909
20m 3/8" 2W Ultrawash Hose	0416	0910
25m 3/8" 2W Ultrawash Hose	0417	0911
30m 3/8" 2W Ultrawash Hose	0418	0912
40m 3/8" 2W Ultrawash Hose	0419	0913