

DRYING CABINETS

Electric Heat Pump Model



MAIN SPECIFICATIONS	7801	7804	7805	7807
Rated Capacity (kg)	4	8	10	10
Evaporation* (g/min)	30	50	55	80
Drying Time Cotton* (min)	67	60	60	69
Rated Input (kW)	1.2	2.3	2.6	2.6
Energy/Load of Linen (Kwh/kg)	0.29	0.35	0.31	0.22
Energy/Water Evaporated (Kwh/l)	0.58	0.70	0.62	0.40
Voltage	230V 1 AC 50-60 Hz	400V 3N AC 50 Hz	220-240V 1 AC 50-60 Hz	400V 3N AC 50 Hz
Sound Level (dB(A))	<70	<70	<70	<70
Size (W x D x H) (mm)	595 x 1910 x 665	1195 x 2060 x 645	1395 x 1915 x 650	1805 x 1805 x 800
Weight (net kg)	95	189	205	250

*Applies to dry weight cotton with 50% residual moisture

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots.

LONG-TERM SAVINGS

By using a Drying Cabinet with a Heat Pump, not only can you avoid exhaust connection you also achieve very low energy consumption. Comes with a built in condensing pump which can handle 0.5m pressure height.

PRODUCTIVITY

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process.

FEATURES

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users.

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- The control panel has braille for the visually impaired
- Large doors and opening angles for easy access
- Extendable hangers for easy loading/unloading
- Flexible installation with adjustable feet

ACCESSORIES



Glove Hanger: More efficient drying of gloves, hats etc



Shoe Rack: Make it easier to dry shoes and boots

CONTACT FOODCLEAN



Discuss how we can help deliver true solutions for your business with one of our experts.

 **T:** +44 (0) 1522 703 703
 **T:** 18668810144
E: sales@foodclean.com
W: www.foodclean.com